

Becher coupling Galvanized steel cardan coupling



Technical specifications:

It's a steel hose coupling which is, first, used with watery medium, for example irrigation water, sewage and tailings.

It can be used on tankers, agricultural water tanks, and septic cars, also with suction and septic hoses.

The sealing is a rubber ring, which is also available in our store.

It can be ordered with different designs; usually the Becher coupling with hose tail is in stock.

Sealing can be ordered with it

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

Female coupling with hose tail (with lever)

Design	Coupling nominal size	Hose inside ø (mm)	Article number
female coupling with hose tail (with lever)	3"	76	191026
female coupling with hose tail (with lever)	4"	102	191043
female coupling with hose tail (with lever)	4"	110	191004
female coupling with hose tail (with lever)	6"	150	191017
female coupling with hose tail (with lever)	8"	200	191002

Apa tömlővéggel (laza galléros)

Kivitel	Csatlakozófej névleges mérete	Tömlő belső ø (mm)	Cikkszám
apa tömlővéggel (laza galléros)	3"	76	191030
apa tömlővéggel (laza galléros)	4"	102	191060
apa tömlővéggel (laza galléros)	4"	110	191005
apa tömlővéggel (laza galléros)	6"	150	191006
apa tömlővéggel (laza galléros)	8"	200	191003



TRIÁSZ-TÖMLŐ KFT.

