

# Betoncord ® / 40 Concrete hose



### Technical specifications:

It is suitable for plaster, mortar, grout and other abrasive and wet medium.

**Felirat:** ® BETONCORD® CONCRETE / BETON PN 40 BAR

**Operating pressure:** 40 bar

**Bursting pressure:** 120 bar

**Heat resistance:** -30°C/+80°C

**Interior:** NR/SBR, black, smooth

**Exterior:** SBR, black, smooth, fabric imprinted

**Linings:** fabric lining

**Electrical resistance:**  $R < 10^6 \Omega$

**Abrasion resistance:** 70 mm<sup>3</sup> according to ISO 4649 (earlier DIN 53516) standard

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Outside Ø (mm) | Roll size (m) | Article number |
|---------------|---------------------|----------------|---------------|----------------|
| 25            | 7                   | 39             | 40            | 3520 025000    |
| 35            | 7                   | 49             | 40            | 3520 035000    |
| 38            | 8                   | 54             | 40            | 3520 038000    |
| 50            | 9                   | 68             | 40            | 3520 050000    |
| 63,5          | 11                  | 85,5           | 40            | 3520 063000    |