

Brass ball valve Both ends with female threads



Technical specifications:

It has complete flow with female threads at both ends. (Type 9000)

Heat range: -15°C/+150°C(üzemi nyomástól függően)

Ball sealing: teflon

Handle: acél, piros lakkozott (2.1/2" és nagyobb méretekben alumínium)

Ball: keménykrómozott réz

Housing: nikkelezett réz

The product is a permanent storage lots. Meantime, we hold the right of selling the stock in products.

| Flow mm | Installation legth | Female thread | PN/bar | Article number |
|---------|--------------------|---------------|--------|----------------|
| 10 | 44,4 | G 1/4 | 50 | 5240 006900 |
| 10 | 44,4 | G 3/8 | 50 | 5240 010900 |
| 15 | 50,5 | G 1/2 | 50 | 5240 013900 |
| 20 | 57,5 | G 3/4 | 40 | 5240 019900 |
| 25 | 70 | 250 bar | 40 | 5240 025900 |
| 32 | 80,5 | G 1.1/4 | 30 | 5240 032900 |
| 40 | 94 | +150 C | 30 | 5240 038900 |
| 50 | 112,5 | G 2 | 25 | 5240 050900 |
| 65 | 134,5 | G 2.1/2 | 18 | 5240 063900 |
| 80 | 157 | G 3 | 16 | 5240 075900 |
| 100 | 190 | G 4 | 14 | 5240 100900 |