

BRIDGE CLAMP Quick release closure CLAMP 213



Technical specifications:

PROPERTIES

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

DESIGN

- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; Clamp wire: stainless steel 1.4310 = AISI 301 (INOX); Screw: stainless steel 1.4301 = AISI 304; Body: stainless steel 1.4016 = AISI 430

DELIVERY VARIANTS

- further diameters available on request

SUITABLE FOR HOSE

- AIRDUC®: 341 + 345 + 363; 350 (AS /FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 355 AS; 362 (FOOD / EC); PROTAPÉ®: 326 + 327 MEMORY; 330 (FOOD / AS BLACK / INOX FOOD -AS); 301 AS; 310 + 320 + 321; 322 EC; 332 SE;
- CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC); TIMBERDUC®: 531 - 533 AS

On stock at the manufacturer, short delivery time with regular shipments

Hose ID (mm)	Article Nr.
60	213-0060-0000
70	213-0070-0000
75	213-0075-0000
80	213-0080-0000
90	213-0090-0000
100	213-0100-0000
110	213-0110-0000
115	213-0115-0000
120	213-0120-0000
125	213-0125-0000
130	213-0130-0000
140	213-0140-0000
150	213-0150-0000

Hose ID (mm)**Article Nr.**

160

213-0160-0000

175

213-0175-0000

180

213-0180-0000

200

213-0200-0000

Image not found or type unknown

