

BRIDGE CLAMP Quick release closure CLAMP 213 - COPY



Technical specifications:

PROPERTIES

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

DESIGN

- Quality: W2; Clamp strip: stainless steel 1.4301 = AISI 304; Screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; Bridge: stainless steel 1.4301 = AISI 304 (INOX)
- in accordance with DIN 3017
-

DELIVERY VARIANTS

- further diameters available on request (MOQ)

SUITABLE FOR HOSE

- AIRDUC®: 341 + 345 + 363; 350 (AS/ FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT-PUR); 351 + 355 EC; 352 SE RAILWAY; 355 AS; 362 (FOOD / EC);
- PROTAPE®: 330 (FOOD / BLACK / INOX FOOD -AS); 301 AS; 310 + 320 + 321 + 326 + 327 + 332; 322 EC;

On stock at the manufacturer, short delivery time with regular shipments

Airduc, Protape max. DN 44 mm

Hose DN (mm)	Band width (mm)	Clamping range (mm)	Cikkszám
13-16	5	9-19	212-0009-0000
15-18	5	13-20	212-0013-0000
18-26	5	17-27	212-0017-0000
22-28	5	20-28	212-0020-0000
25-29	9	22-37	212-0022-0000
30-35	9	27-47	212-0027-0000
32-37	9	29-47	212-0029-0000
38-44	9	35-55	212-0035-0000

CP 38-65 mm, Protape TPE 326 Memory 51-65 mm

Hose DN (mm)	Band width (mm)	Clamping range (mm)	Cikkszám
38-45	9	35-55	212-0035-2002

Hose DN (mm)	Band width (mm)	Clamping range (mm)	Cikkszám
50-55	9	45-65	212-0045-2002
60-65	9	55-75	212-0055-2002

Airduc, Protape 45 mm-től, CP, Protape TPE Memory 70 mm

Hose DN (mm)	Band width (mm)	size range (mm)	Article Nr.
45-50	9	40-60	212-0040-0000
50-55	9	45-65	212-0045-0000
60-65	9	55-75	212-0055-0000
70-75	9	65-85	212-0065-0000
80-85	9	75-95	212-0075-0000
90-95	9	85-105	212-0085-0000
100-105	9	95-115	212-0095-0000
110-115	9	105-125	212-0105-0000
120-125	9	115-135	212-0115-0000
130-135	9	125-145	212-0125-0000
140-145	9	135-155	212-0135-0000
150-155	9	145-165	212-0145-0000
160-165	9	155-175	212-0155-0000
170-175	9	165-185	212-0165-0000
180-185	9	175-195	212-0175-0000
190-195	9	185-205	212-0185-0000
200-205	9	195-215	212-0195-0000
210-215	12	205-225	212-0205-0000
220-225	12	215-235	212-0215-0000
250-255	12	245-265	212-0245-0000
260-265	12	255-275	212-0255-0000
270-275	12	265-275	212-0265-0000
280-285	12	275-295	212-0275-0000
300-305	12	295-315	212-0295-0000
310-315	12	305-325	212-0305-0000
320-325	12	315-335	212-0315-0000
350-355	12	345-365	212-0345-0000
370-375	12	365-385	212-0365-0000
400-405	12	395-415	212-0395-0000
450-455	12	445-465	212-0445-0000
500-505	12	495-515	212-0495-0000
510-535	12	505-545	212-0505-0000
550-575	12	545-585	212-0545-0000
630-655	12	625-665	212-0625-0000



TRIÁSZ-TÖMLŐ KFT.

