

Carbocord / EN Oil and petrol resistant discharge hose



Technical specifications:

It's persistent against mineral oil products, up to max 50% aroma content.
It's really suitable for tanker truck cars, biodiesel and E10.

Felirat: ® CARBOCORT® EN 12115:2011 NBR 1 - D - SIZE - PN 16 BAR -
QT - TRBF 131/T2 - P.5.5 - QUARTER/YEAR

Operating pressure: 16 bar

Bursting pressure: 64 bar

Heat resistance: -30°C /+90°C

Interior: NBR, black, smooth

Exterior: CR, black, fabric imprinted

Electrical resistance: 10^6

Dielectric strength: 10^9

Standard: EN 12115 and TRbF131 part 2, 5.5 §

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Outside Ø (mm) | Roll size (m) | Article number |
|---------------|---------------------|----------------|---------------|----------------|
| 32 | 6 | 44 | 40 | 3380 032000 |
| 38 | 6,5 | 51 | 40 | 3380 038000 |
| 50 | 8 | 66 | 40 | 3380 050000 |
| 75 | 8 | 91 | 40 | 3380 075000 |
| 100 | 8 | 116 | 40 | 3380 100000 |