

Carbocord ® / 10 Oil and petrol resistant discharge hose



Technical specifications:

Oil and petrol delivery hose which is suitable for multi purposes. It's persistent against mineral oil products, up to max 50% aroma content.

The hose is often used during the loading and unloading of unleaded fuels with a maximum aromatic content up to 50% in fuel tanks and ships. Suitable for industrial oils, biodiesel, fuels oils and mineral based hydraulic oils.

The hose inner tube is conductive, the cover anti-static.

Felirat: ® CARBOCORD® - NBR - DRUCK / DISCHARGE - PN 10 BAR - Ω

Working pressure: 10 bar

Burst pressure: 30 bar

Temperature: -40°C /+90°C max. olaj hőfok 100 C

Inside: NBR, fekete, sima, Elektromosan vezetőképes R<10⁶ Ω

Outside: SBR/EPDM, fekete, szövetlenyomatos, antisztatikus R<10⁹ Ω

Insertions: textile plies

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Inside diamter (mm) | Wall thickness (mm) | Outer diameter (mm) | Bending radius (mm) | Weight (kg/m) | Coil length | Article Nr. |
|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------|--------------------|--------------------|
| 32 | 6 | 44 | 210 | 1 | 40 | 3310 032000 |
| 38 | 6,5 | 51 | 300 | 1,28 | 40 | 3310 038000 |
| 50 | 7 | 64 | 400 | 1,75 | 40 | 3310 050000 |