

Carboflex /10 / Raffineria Suction/discharge hose



Technical specifications:

It is persistent against mineral oil products, up to max. 50% aroma content.

It is suitable for the suction of mineral oils and petrol. It has a light weight and flexible design with a small bending radius.

The hose is usually used with truck recharging and canal cleaning vehicles.

Felirat: ® CARBOFLEX® NBR - ÖL SAUG/DRUCK - OIL
SUCTION/DISCHARGE - PN 10 BAR - Ω

Heat resistance: -30°C / +80°C (for short time +120°C depending on the medium)

Interior: NBR, black, electrically conductive

Exterior: synthetic rubber, black, corrugated, abrasion resistant, ozone and ageing resistant, fabric imprinted, for a short it can contact mineral oils and hydrocarbon

Roll size (m): 50 m

Vacuum: -0,9 bar

Reinforcement: really flexible synthetic rubber with embedded static wire

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Outside Ø (mm)	Wall thickness (mm)	Bending radius (mm)	Weight (kg/m)	Roll size (m)	Article number
32	43	5,5	100	0,9	40	104127
38	50	6	120	1,1	40	104128
40	52	6	120	1,15	40	104129
45	59	7	150	1,48	40	104130
50	64	7	180	1,6	40	104131
63,5	77,5	7	250	2,05	40	104132
70	85	7,5	280	2,43	40	104133
75	90	7,5	300	2,6	40	104125
80	95	7,5	320	2,73	40	104134
90	106	8	360	3,34	40	104135
100	116	8	400	3,67	40	104126
102	118	8	400	3,73	40	104136