

Carboflex / U.L. / OHM Lightweight, oil and petrol resistant suction hose



Technical specifications:

Highly flexible and lightweight oil and petrol suction and discharge hose with electrical conductive properties.

Due to its special flat corrugated and lightweight construction the Carboflex/U.L./Ohm is an extremely flexible and easy to handle oil suction and discharge hose. The hose meets all SIR guidelines and can be used in various ATEX zones. Very suitable for vehicles and activities in industrial cleaning, tank transport or other activities where the person on the hose prefers to work with a light weight product which is also recommended from the health and safety legislation. Suitable for transport of industrial oils, heating oils, biodiesel, mineral based hydraulic oils and unleaded fuels with a maximum aromatic content up to 50%.

Felirat: ® TURBOFLEX/UL/OHM - SAUG/DRUCK - SUCTION/DISCHARGE - ABRIEB/ABRASION 60 MM3 - WP 5 BAR - BP 15 BAR - Ω

Working pressure: 5 bar

Bursting pressure: 15 bar

Vacuum: -0,9 bar

Temperature: -40°C / +90 °C (+100 C olajra)

Norm: EN ISO 1307:2008, TRbF 131, part 2, § 5.5

Inside: fekete, sima, NBR, vezetőképes

Outside: Fekete, laposan hullámos, CR

Insertions: Acél spirál, szövet betétek

Conductivity: $10^6 \Omega$

Elektr. Resistance tube to cover: Antistatic $10^9 \Omega$

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

ID	wall	OD	kg/m	Bending radius	Coil length	Article code
51	5,5	62	1,38	130	40	3354 050000
76	6	88	2,24	190	40	3354 075000
102	6,5	115	3,29	255	40	3354 100000
152	8,5	169	6,34	460	20	3354 150000