

# Carboflex ® / EN Oil and petrol resistant suction/discharge tanker truck hose



## Technical specifications:

It's persistent against mineral oil products, up to max 50% aroma content.

**Felirat:** ® CARBOFLEX® - MANUFACTURERS NAME EN 12115:2011 NBR-1 - SD - PN.. - WP 16 BAR - Q/T - TRBF 131/T2 P5.5 - QUARTER/YEAR

**Operating pressure:** 16 bar

**Bursting pressure:** 64 bar

**Heat resistance:** -30°C/+90°C

**Interior:** NBR? Black, smooth

**Exterior:** CR, black, fabric imprinted

**Linings:** steel wire helix

**Vacuum:** -0,9 bar

**Electrical resistance:** < 106 Ω

**Átmenő ellenállás:** < 109 Ω

**Standard:** EN 12115:2011 and TRbF131 part 2. 5.5 §

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Tekercsméret (m)	Cikkszám
25	6	37	40	3356 025000
32	6	44	40	3356 032000
38	6,5	51	40	3356 038000
50	8	66	40	3356 050000
63,5	8	79,5	40	3356 063000
75	8	91	40	3356 075000
100	8	116	40	3356 100000