

## Carboform / EN / ISO Oil and petrol resistant discharge hose



### Technical specifications:

The petrol hose was specially developed for ships. The hose is flame retardant and the exterior is self-extinguishing. It's persistent against mineral oil products, up to max 50% aroma content. The hose is suitable for unleaded petrol.

**Felirat:** ® PRODUCER ITALY CARBOPUMP® MARINE FUEL HOSE ISO 7840:2013 A1 E10/B10 COMPATIBLE - CE - SAE J 1527:2011 USCG A1 - RINA - LLOYD'S REGISTER - YEAR - DN

**Heat resistance:** -20°C/+80°C

**Interior:** NBR, black, smooth

**Exterior:** CR, black, smooth, flame retardant

**Permeability:** <4g/m<sup>2</sup> per hour

**Standard:** EN/ISO 7840

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Outside Ø (mm)	Weight(kg/m)	Operating pressure/Bursting pressure	Article number
6	15	0,24	8bar / 14 bar	3305 006000
8	16	0,25	8bar / 14 bar	3305 008000
10	18	0,28	8bar / 14 bar	3305 010000
12	21	0,36	3,5 bar / 10 bar	3305 012000
16	26	0,45	3,5 bar / 10 bar	3305 016000
19	29	0,5	3,5 bar / 10 bar	3305 019000