

CONNECT 244



Technical specification

Temperatur

PROPERTIES

resistance: -40/+90 C Short period +125 C

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant

On stock at the manufacturer, short delivery time with regular orders

- good resistance to oil, gasoline and chemicals

- conforms to RoHS guideline

- REACH according to Technology / Technical Information / REACH

Hose DN typ 350, 351, 355, 533, 341, 345	Pipe DN	Hole circle (mm)	Number and size of holes	Total length	Weight (kg)	Article code
50	51,2	125	4x18	66	1,11	244-0050-8500
80	82,5	160	8x18	76	1,74	244-0080-8500
100	100,8	180	8x18	84	2,03	244-0100-8500
125	126	210	8x18	100	3,19	244-0125-8500
150	151	240	8x22	114	4,32	244-0150-8500
200	207,3	295	8x22	132	6,38	244-0200-8500
250	254,4	350	12x22	145	9,75	244-0250-8500
300	309,7	400	12x22	155	13,04	244-0300-8500
SUITABLE FOR HOSE						
BLACK / FOOD-AS); 351 + 355 + 356 (FOOD / INOX FOOD-AS / EC); 355 + 356 AS; TIMBERDUC®: 533 AS						
Hose DN typ 356	Pipe DN	Hole circle (mm)	Number and size of holes	Total length	Weight (kg)	Article code
50	51,2	125	4x18	66	1,11	244-0050-8501
80	82,5	160	8x18	76	1,74	244-0080-8501
100	100,8	180	8x18	84	2,03	244-0100-8501
125	126	210	8x18	100	3,19	244-0125-8501
150	151	240	8x22	114	4,32	244-0150-8501
200	207,3	295	8x22	132	6,38	244-0200-8501
250	254,4	350	12x22	145	9,75	244-0250-8501
300	309,7	400	12x22	155	13,04	244-0300-8501



TRIÁSZ-TÖMLŐ KFT.

