

EVA 373 EC Vacuum cleaner hose, electrically conductive $<10^6 \Omega$



Technical specifications:

APPLICATIONS

- flexible hose/ ducting for gases and for dust, powder, fibres
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- swimming pool cleaning
- scrubber, floor cleaning machine

PROPERTIES

- light weight
- highly flexible
- crush resistant
- floatable
- good resistance to alkalis and acids
- surface resistance $<10^6 \Omega$
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dusts (Zone 22 inside), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in Zone 0 (gases)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

TEMPERATURE RANGE

- -25°C to 65°C

DELIVERY VARIANTS

- further diameters and lengths available on request
- black (standard)

DESIGN

- EVA design
- 1. self-supporting profile design
- 2. open profile geometry; wall: EVA

Cutting not possible.

Temperature: $-25/+65 \text{ C}$

Construction: EVA, self-supporting profile design, black

coil length: 30 m

Vákuum: -0,5 bar

surface resistance: $<10^{11} \Omega$

Color: Fekete

On stock at the manufacturer, short delivery time with regular shipments

ID	Outside diameter (mm)	Bending radius (mm)	Kg/m	Article code
25	32.20	54.00	0.15	373-0025-1002
32	40.40	66.00	0.24	373-0032-1002
35	43.80	71.00	0.26	373-0035-1002
38	47.20	74.00	0.31	373-0038-1002
40	49.40	80.00	0.32	373-0040-1002
45	55.00	89.00	0.37	373-0045-1002
50	60.40	97.00	0.44	373-0050-1002
60	72.00	113.00	0.67	373-0060-1002

