

GRANUFLEX NORPLAST® PUR 385 AS



Technical specifications:

Applications

- flexible hose for granulate, powder and bulk material
- wood pellet heating system: conveying of wood pellets
- textile industry: fiber extraction (on spinning/knitting and weaving machines)
- construction industry: insulation-blowing system

Properties

- abrasion resistant medium-heavy duty
- environmentally friendly due to the absence of soft PVC
- 6 times better abrasion resistance compared to the PVC version
- lower static friction due to mirror-smooth PU inner tube

Temperature Range

- -25°C to 85°C

Delivery variants

- transparent inner tube with anthracite-colored hard PVC spiral

Design

- NORPLAST® full plastic hose
- rigid PVC spiral
- grounding wire
- smooth interior
- wall: premium polyurethane (Pre-PUR®)

Felirat: NORPLAST PUR 385 AS GRANUFLEX - size - lot

Temperature: -25°C/+85°C

Construction: Belül PU, tükörsima, átlátszó, antracitszürke kemény PVC spirállal, és földelhető sztatikus részzel

outside: Hullámos

Bending radius: 1× belső Ø

Norm: EN ISO 1307:2008

On stock at the manufacturer, short delivery time with regular shipments

| ID mm | PU wall thickness (mm) | OD mm | Bending radius | kg/m | Coil length m | Article Nr. |
|-------|------------------------|-------|----------------|------|---------------|-------------|
| 38 | 0,7 | 45 | 38 | 0,34 | 30 | 4609038000 |
| 40 | 0,7 | 47 | 40 | 0,35 | 30 | 4609040000 |
| 45 | 0,7 | 53 | 45 | 0,43 | 30 | 4609045000 |
| 51 | 0,8 | 59 | 51 | 0,45 | 30 | 4609050000 |

| ID mm | PU wall thickness (mm) | OD mm | Bending radius | kg/m | Coil length m | Article Nr. |
|-------|------------------------|-------|----------------|------|---------------|-------------|
| 60 | 0,8 | 68 | 60 | 0,6 | 30 | 4609060000 |

