

Guillemin coupling with male thread Made of aluminium or stainless steel



Technical specifications:

Also called as French coupling, the material of it is stainless steel or aluminium and has an NBR (oil resistant) sealing ring.

Operating pressure: 16 bar

Aluminium

| Male thread | Nominal size | Material | Article number |
|-------------|--------------|-----------|----------------|
| G 3/4" | 20 | Aluminium | 5730 019019 |
| G 1" | 25 | Aluminium | 5730 025025 |
| G 1. 1/4" | 32 | Aluminium | 5730 032032 |
| G 1. 1/2" | 40 | Aluminium | 5730 038038 |
| G 2" | 50 | Aluminium | 5730 050050 |
| G 2. 1/2" | 65 | Aluminium | 5730 063063 |
| G 3" | 80 | Aluminium | 5730 075075 |
| G 4" | 100 | Aluminium | 5730 100100 |

Stainless steel

| Male thread | Nominal size | Material | Article number |
|-------------|--------------|-----------------|----------------|
| G 3/4" | 20 | Stainless steel | 5742 019019 |
| G 1" | 25 | Stainless steel | 5742 025025 |
| G 1. 1/4" | 32 | Stainless steel | 5742 032032 |
| G 1. 1/2" | 40 | Stainless steel | 5742 038038 |
| G 2" | 50 | Stainless steel | 5742 050050 |

| Male thread | Nominal size | Material | Article number |
|-------------|--------------|-----------------|----------------|
| G 2. 1/2" | 65 | Stainless steel | 5742 063063 |
| G 3" | 80 | Stainless steel | 5742 075075 |
| G 4" | 100 | Stainless steel | 5742 100100 |