

## HEDUFLEX GRECATO Rubber suction hose



### Technical specifications:

Rubber suction and discharge hose with corrugated cover for drainage water, dung and with limited lye and acid resistance. Very high quality, extra flexible rubber hose. Suitable for (industrial) water and dung. Limited lye and acid resistant. Widely used for industrial, agricultural, machine building, construction, infrastructure and horticultural applications. The hose is very flexible due to the special "Greek" profile and is therefore often used in places where a very small bending radius is required.

**Felirat:** Marking: Heduflex®/Grecato S/D PN 6 bar

**Working pressure:** 6 bar

**Burst pressure:** 18 bar

**Vacuum:** -0,9 bar

**Temperatur resistance:** -30°C / +85 °C

**Inside:** SBR rubber, black, smooth

**Outside:** SBR Rubber, black, square corrugated, fabric finish

**Insertions:** Textile plies, Steel spiral

**Norm:** EN ISO 1307:2008

Just for order!

Inside diameter (mm)	Wall thickness (mm)	Outer diameter (mm)	Bending radius (mm)	coil length (m)	Article Nr.
76	7	90	228	40	3641 075000
102	7,5	117	306	40	3641 100000
127	8	143	445	20	3641 125000
152	8	168	608	20	3641 150000
203	10,5	224	812	4	3641 200000
203	10,5	224	812	6	3641 200000