

HEDUFLEX Rubber spiral hose



Technical specifications:

Rubber suction and discharge hose for drainage water, dung and with limited lye and acid resistance.

High-quality rubber hose. One of the bestselling products for heavy duty industrial applications, agriculture, construction, infrastructure and gardening. Hose is also very widely used on the suction side of pumps, where the thick wall strength, robust construction and wear-resistant cover contribute to a very long life time of this hose. Other dimensions can be produced on request.

Felirat: Marking: Heduflex® S/D PN 10 bar (203/254/305 MM PN 6 bar)

Üzemi nyomás: 10 bar – Ø 203-254-305 mm 6 bar

Repesztési nyomás: 30 bar – Ø203-254-305 mm 18 bar

Vákuum: -0,9 bar

Hőállóság: -30°C / +80 °C

Belül: SBR gumi, fekete, sima

Kívül: SBR gumi, fekete, sima, szövetnyomatos

Betétek: Textil szövetbetétekkel, és acélspirállal

Szabvány: EN ISO 1307:2008

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Üzemi nyomás (bar)	Hajlítási sugár (mm)	Tekercsméret (m)	Cikkszám
19	5,5	30	10	95	40	3640 019000
25	5	35	10	125	40	3640 025000
32	5,5	43	10	160	40	3640 032000
38	6	50	10	190	40	3640 038000
40	6	52	10	200	40	3640 040000
51	6,5	64	10	210	40	3640 050000
60	6,5	73	10	240	40	3640 060000
63	8	79	10	260	40	3640 063000
76	7	90	10	310	40	3640 075000
76	7	90	10	310	20	3640 075000
80	7,5	95	10	320	40	3640 080000
90	7,5	105	10	360	40	3640 090000
102	7	116	10	410	40	3640 100000
102	7	116	10	410	20	3640 100000



TRIÁSZ-TÖMLŐ KFT.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Üzemi nyomás (bar)	Hajlítási sugár (mm)	Tekercsméret (m)	Cikkszám
110	8	126	10	440	20	3640 110000
127	8,5	144	10	510	20	3640 125000
152	9	170	10	760	20	3640 150000
203	10,5	224	6	1015	5	3640 200000
203	10,5	224	6	1015	6	3640 200000
254	10,5	275	6	1270	5	3640 250000
254	10,5	275	6	1270	6	3640 250000
305	10,5	326	6	1830	5	3640 300000
305	10,5	326	6	1830	3	3640 300000

