

HEDUFLEX Rubber spiral hose



Technical specifications:

Rubber suction and discharge hose for drainage water, dung and with limited lye and acid resistance.

High-quality rubber hose. One of the bestselling products for heavy duty industrial applications, agriculture, construction, infrastructure and gardening. Hose is also very widely used on the suction side of pumps, where the thick wall strength, robust construction and wear-resistant cover contribute to a very long life time of this hose. Other dimensions can be produced on request.

Felirat: Marking: Heduflex® S/D PN 10 bar (203/254/305 MM PN 6 bar)

Üzemi nyomás: 10 bar – Ø 203-254-305 mm 6 bar

Repesztési nyomás: 30 bar – Ø203-254-305 mm 18 bar

Vákuum: -0,9 bar

Hőállóság: -30°C / +80 °C

Belül: SBR gumi, fekete, sima

Kívül: SBR gumi, fekete, sima, szövetnyomatos

Betétek: Textil szövetbetétekkel, és acélspirállal

Szabvány: EN ISO 1307:2008

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Belső Ø (mm) | Falvastagság (mm) | Külső Ø (mm) | Üzemi nyomás (bar) | Hajlítási sugár (mm) | Tekercsméret (m) | Cikkszám |
|--------------|-------------------|--------------|--------------------|----------------------|------------------|-------------|
| 19 | 5,5 | 30 | 10 | 95 | 40 | 3640 019000 |
| 25 | 5 | 35 | 10 | 125 | 40 | 3640 025000 |
| 32 | 5,5 | 43 | 10 | 160 | 40 | 3640 032000 |
| 38 | 6 | 50 | 10 | 190 | 40 | 3640 038000 |
| 40 | 6 | 52 | 10 | 200 | 40 | 3640 040000 |
| 51 | 6,5 | 64 | 10 | 210 | 40 | 3640 050000 |
| 60 | 6,5 | 73 | 10 | 240 | 40 | 3640 060000 |
| 63 | 8 | 79 | 10 | 260 | 40 | 3640 063000 |
| 76 | 7 | 90 | 10 | 310 | 40 | 3640 075000 |
| 76 | 7 | 90 | 10 | 310 | 20 | 3640 075000 |
| 80 | 7,5 | 95 | 10 | 320 | 40 | 3640 080000 |
| 90 | 7,5 | 105 | 10 | 360 | 40 | 3640 090000 |
| 102 | 7 | 116 | 10 | 410 | 40 | 3640 100000 |
| 102 | 7 | 116 | 10 | 410 | 20 | 3640 100000 |



TRIÁSZ-TÖMLŐ KFT.

| Belső Ø (mm) | Falvastagság (mm) | Külső Ø (mm) | Üzemi nyomás (bar) | Hajlítási sugár (mm) | Tekercsméret (m) | Cikkszám |
|-----------------|-------------------|-----------------|-----------------------|-------------------------|------------------|-------------|
| 110 | 8 | 126 | 10 | 440 | 20 | 3640 110000 |
| 127 | 8,5 | 144 | 10 | 510 | 20 | 3640 125000 |
| 152 | 9 | 170 | 10 | 760 | 20 | 3640 150000 |
| 203 | 10,5 | 224 | 6 | 1015 | 5 | 3640 200000 |
| 203 | 10,5 | 224 | 6 | 1015 | 6 | 3640 200000 |
| 254 | 10,5 | 275 | 6 | 1270 | 5 | 3640 250000 |
| 254 | 10,5 | 275 | 6 | 1270 | 6 | 3640 250000 |
| 305 | 10,5 | 326 | 6 | 1830 | 5 | 3640 300000 |
| 305 | 10,5 | 326 | 6 | 1830 | 3 | 3640 300000 |

