

## **CP HiTex 467 Welding Clamp profile hose (clip hose) for flying sparks or welding sparks, (to +280°C)**



### **Technical specifications:**

#### **APPLICATIONS**

- flexible hose/ ducting for gases and for dust, powder, fibres
- welding fume extraction
- extraction arm

#### **PROPERTIES**

- very good resistance to flying sparks and welding sparks
- fabric reinforced
- abrasion protection via external clamp profile
- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- extremely heat resistant
- flame-retardant
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

#### **TEMPERATURE RANGE**

- -70°C to 260°C
- short time to 280°C

#### **DELIVERY VARIANTS**

- further diameters and lengths available on request
- black (standard)
- stainless steel (INOX) clamp profile
- double-layer

#### **DESIGN**

- CP construction
- 1. clamp profile supporting spiral: galvanised steel
- 2. fabric-reinforced tape; wall: special-coated high-temperature fabric

**Temperatur resistance:** -70°C / +260°C (rövid ideig +280°C)

**Construction:** nagy hőállóságú többrétegű szövet

**Inside:** Fekete

**outside:** Fekete, külső hoganyzott acél spirállal

**Manufacturing length:** 3 és 6 m – más hosszokban is gyártható

Will be manufactured with short delivery time. MOQ 3 m

| Inner diameter<br>(mm) | Outer diameter<br>(mm) | Working pressure<br>(bar) | Vacuum (bar) | Bending radius<br>(mm) | Article Nr.   |
|------------------------|------------------------|---------------------------|--------------|------------------------|---------------|
| 80                     | 92                     | 0,6                       | 0,12         | 24                     | 467-0080-0000 |
| 100-102                | 112                    | 0,52                      | 0,09         | 28                     | 467-0100-0000 |
| 120                    | 132                    | 0,35                      | 0,06         | 32                     | 467-0120-0000 |
| 150-152                | 162                    | 0,22                      | 0,04         | 38                     | 467-0150-0000 |
| 200-203                | 212                    | 0,15                      | 0,02         | 48                     | 467-0200-0000 |
| 250                    | 262                    | 0,1                       | 0,012        | 58                     | 467-0250-0000 |
| 350                    | 362                    | 0,055                     | 0,006        | 78                     | 467-0350-0000 |

