

CP HiTex 467 Welding Clamp profile hose (clip hose) for flying sparks or welding sparks, (to +280°C) - COPY - COPY



Technical specifications:

APPLICATIONS

- flexible hose/ ducting for gases and for dust, powder, fibres
- welding fume extraction
- extraction arm

PROPERTIES

- very good resistance to flying sparks and welding sparks
- fabric reinforced
- abrasion protection via external clamp profile
- secure clamping of the wall within the clamp profile
- highly flexible + compressible 4:1
- extremely heat resistant
- flame-retardant
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

TEMPERATURE RANGE

- -70°C to 260°C
- short time to 280°C

DELIVERY VARIANTS

- further diameters and lengths available on request
- black (standard)
- stainless steel (INOX) clamp profile
- double-layer

DESIGN

- CP construction
- 1. clamp profile supporting spiral: galvanised steel
- 2. fabric-reinforced tape; wall: special-coated high-temperature fabric

: -30 °C / +220 °C

Felépítés: Szilikon bevonatú üvegszövet

Kívül: Külső hoganyzott acél spirállal

Tekercsméret: 3 és 6 m – más hosszokban is gyártható

Will be manufactured with short delivery time. MOQ 3 m

Belső Ø (mm)	Külső átmérő (mm)	Üzemi nyomás (bar)	Vacuum (bar)	Hajlítási sugár (mm)	Cikkszám
50-51	62	0,49	0,27	18	457-0050-1003

Belső Ø (mm)	Külső átmérő (mm)	Üzemi nyomás (bar)	Vacuum (bar)	Hajlítási sugár (mm)	Cikkszám
55	67	0,46	0,25	20	457-0055-1003
60	72	0,44	0,22	20	457-0060-1003
63-65	77	0,42	0,2	22	457-0065-1003
70	82	0,4	0,18	22	457-0070-1003
75-76	87	0,38	0,16	24	457-0075-1003
80	92	0,365	0,14	24	457-0080-1003
89-90	102	0,34	0,1	26	457-0090-1003
100-102	112	0,225	0,085	28	457-0100-1003
110	122	0,21	0,075	30	457-0110-1003
114-115	127	0,205	0,07	32	457-0115-1003
120	132	0,2	0,065	32	457-0120-1003
125-127	137	0,195	0,06	34	457-0125-1003
150-152	162	0,12	0,035	38	457-0150-1003
160	172	0,115	0,03	40	457-0160-1003
180	192	0,11	0,025	44	457-0180-1003
200-203	212	1	0,02	48	457-0200-1003
250	262	0,07	0,015	58	457-0250-1003
254	266	0,065	0,015	59	457-0254-1003
300	312	0,06	0,01	68	457-0300-1003
305	317	0,055	0,01	69	457-0305-1003
315	327	0,05	0,01	71	457-0315-1003
350	362	0,045	0,01	78	457-0350-1003





TRIASZ-TÖMLŐ KFT.

