

## Kehrflex Street vacuum cleaner hose with steel wire helix



### Technical specifications:

It is an abrasive resistant, inside and outside corrugated hose with a green natural caoutchouc interior. The cover is a weather resistant, anti-static, corrugated NR material. The hose is longitudinal slightly compressible, flexible.

Both end has a +/-100 mm long spiral free cuff. Special convoluted hose in street sweeping machines for suction of leaves, grass and general debris

**Inside:** Green, corrugated, abrasion resistant, NR – Naturkauchuk

**Abrasion value Inside according DIN 53516:** 250 mm<sup>3</sup>

**Temperature:** -30/+85 C

**Outside:** NR, black, corrugated, cloth impression, antistatic, resistant to weather, ozone and abrasion

**Abrasion value outside according DIN 53516:** 60 mm<sup>3</sup>

**Ends:** Both ends with soft cuffs

**Electrical conductivity cover:** R<10 6 Ω/m

Just for order!

| Inner diameter (mm) | Outer diameter (mm) | Wall thickness (mm) | Max. Vacuum (bar) | Bending radius mm | Weight kg/m | Possible length m | Article Nr. (* means the length) |
|---------------------|---------------------|---------------------|-------------------|-------------------|-------------|-------------------|----------------------------------|
| 120                 | 130                 | 5                   | -0,4              | 240               | 3,8         | 4,5               | 3612 120450                      |
| 152                 | 162                 | 5                   | -0,4              | 304               | 4,32        | 1,47-2            | 3612 152***                      |
| 200                 | 210                 | 5                   | -0,4              | 400               | 6,01        | 0,6               | 3612 200060                      |
| 203                 | 213                 | 5                   | -0,4              | 406               | 6,51        | 0,48-4            | 3612 203***                      |
| 210                 | 220                 | 5                   | -0,3              | 420               | 6,7         | 1,85              | 3612 210185                      |
| 220                 | 230                 | 5                   | -0,3              | 440               | 6,95        | 0,75-1,9          | 3612 220***                      |
| 220                 | 232                 | 6                   | -0,3              | 440               | 6,95        | 1,47-2            | 3613 220***                      |
| 225                 | 235                 | 5                   | -0,3              | 450               | 7,08        | 0,86              | 3612 225086                      |
| 230                 | 240                 | 5                   | -0,3              | 460               | 6,32        | 0,87-1,5          | 3612 230***                      |
| 254                 | 264                 | 5                   | -0,3              | 508               | 8,65        | 0,55-8            | 3612 254***                      |
| 254                 | 270                 | 8                   | -0,3              | 508               | 9,41        | 6                 | 3613 254600                      |
| 280                 | 290                 | 5                   | -0,2              | 560               | 7,15        | 1,48              | 3612 280148                      |
| 300                 | 310                 | 5                   | -0,2              | 600               | 8,53        | 1,5-2             | 3612 300***                      |
| 300                 | 314                 | 7                   | -0,2              | 600               | 9,54        | 1,2-1,75          | 3613 300***                      |
| 350                 | 360                 | 5                   | -0,2              | 700               | 10,16       | 0,74              | 3612 350074                      |
| 400                 | 415                 | 7,5                 | -0,2              | 800               | 16,71       | 3,6               | 3612 400360                      |



TRIÁSZ-TÖMLŐ KFT.

