

## Naftoil / Buna PVC/NBR suction/discharge hose



### Technical specifications:

It's suitable for service and mineral water, even with difficult working environment.

**It's really flexible, even in cold weather.**

**Bending radius: inside diameter x 3 !!**

**Felirat:** ® NAFTOIL / BUNA - Ø SIZE- PROD. CODE

**Heat resistance:** -30°C/+65°C

**Structure:** PVC/NBR mix, gray, embedded PVC spiral

**Vacuum:** -0,9 bar

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Wall thickness (mm)	Outside Ø (mm)	Pressure on 20°C (bar)	Weight (kg/m)	Roll size (m)	Article number
25	4	33	7	0,44	50	4465 025000
32	4,5	41	6	0,6	50	4465 032000
38	5	48	6	0,7	50	4465 038000
51	5	61	5	0,98	50	4465 050000
63	5,5	74	4,5	1,2	50	4465 063000
76	6	88	4	1,6	50	4465 075000
80	6	92	3	1,7	50	4465 080000
90	7	104	3	2,2	50	4465 090000
102	7	116	3	2,4	50	4465 100000
127	8	143	2	3,3	20	4465 125000
152	8,5	169	2	4,2	20	4465 150000