

Naftrex / B Petrol hose DIN 73379



Technical specifications:

The petrol hose has a vulcanized fabric exterior coating.

Felirat: DIN 73379 DIAMETER GERMANY

Operating pressure: 10 bar

Bursting pressure: 30 bar

Heat resistance: -35°C / +90°C (for short time +100°C)

Interior: NBR, black, smooth

Exterior: black vulvanized fabric cover

Diesel: +80°C

Cooling liquid (glocol, glizantin.. etc): +90°C

Ari: +80°C

High oktane number gasoline: +40°C

Standard: DIN 73379

Gasoline containing max 50% benzol: +40°C

Water: +90°C

Water oxidising material: +80°C

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Wall thickness (mm)	Outside Ø (mm)	Roll size (m)	Article number
3,2	1,9	7	20	3370 032070
3,5	2	7,5	20	3370 035075
4	2,5	9	20	3370 040090
4,5	2,5	9,5	20	3370 045095
5	2,5	10	20	3370 050100
5,5	2,5	10,5	20	3370 055105
6	2,5	11	20	3370 060110
7	2,5	12	20	3370 070120
7,5	2,5	12,5	20	3370 075125
8	2,5	13	20	3370 080130
9	2,5	14	20	3370 090140
11,5	2,75	17	20	3370 115170