

## Naftrex / B Petrol hose DIN 73379



### Technical specifications:

The petrol hose has a vulcanized fabric exterior coating.

**Felirat:** DIN 73379 DIAMETER GERMANY

**Operating pressure:** 10 bar

**Bursting pressure:** 30 bar

**Heat resistance:** -35°C / +90°C ( for short time +100°C)

**Interior:** NBR, black, smooth

**Exterior:** black vulvanized fabric cover

**Diesel:** +80°C

**Cooling liquid (glocol, glizantin.. etc):** +90°C

**Ari:** +80°C

**High oktane number gasoline:** +40°C

**Standard:** DIN 73379

**Gasoline containing max 50% benzol:** +40°C

**Water:** +90°C

**Water oxidising material:** +80°C

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Wall thickness (mm)	Outside Ø (mm)	Roll size (m)	Article number
3,2	1,9	7	20	3370 032070
3,5	2	7,5	20	3370 035075
4	2,5	9	20	3370 040090
4,5	2,5	9,5	20	3370 045095
5	2,5	10	20	3370 050100
5,5	2,5	10,5	20	3370 055105
6	2,5	11	20	3370 060110
7	2,5	12	20	3370 070120
7,5	2,5	12,5	20	3370 075125
8	2,5	13	20	3370 080130
9	2,5	14	20	3370 090140
11,5	2,75	17	20	3370 115170