

# NEO-COAT 1 Heat-resistant, up to 135 °C, thin-walled suction hose



### Technical specifications:

The hose is UV and chemical resistant and extremely flexible with helix reinforcement. It's suitable for hot steam and gas suction.

There is a hose with thicker wall, where the spiral is covered.

There is a similar hose with a longer design.

**Heat resistance:** -36°C / +135°C (for short time +150°C)

**Structure:** Neoprene coated glass fibre with steel spiral

**Roll size:** 4 m

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Bending radius (mm)	Vacuum (bar)	Pressure (bar)	Article number
25	12	0,53	1,4	246031
32	16	0,5	1,4	246032
38	19	0,5	1,4	246033
51	25	0,44	1,2	246028
60	30	0,4	1,1	246034
63	31	0,4	1,1	246035
70	35	0,35	1,1	246002
80	40	0,3	1	246036
83	41	0,3	1	246037
90	45	0,3	0,9	246003
95	47	0,27	0,9	246038
102	51	0,26	0,9	246039
120	66	0,17	0,8	246060
140	70	0,15	0,8	246040
152	76	0,15	0,8	246042



TRIÁSZ-TÖMLŐ KFT.

