

PROTAPE PUR 330 AS 0,6 mm ATEX, light suction hose Antistatic polyurethane hose, light, microbe resistant + flame-resistant



Technical specifications:

APPLICATIONS

- flexible hose/ ducting for gases and for abrasive dust, powder, fibres
- printed circuit board drilling machine (PCB)
- extraction unit, dedusting system, filter system, oil mist extraction
- extraction arm
- chemical industry: chemical vapours, vapour return hose at loading arm, paint steam, spray mist extraction
- explosion hazard area
- animal stall, animal shed: barn ventilation
- clean room ventilation, semiconductor production machine
- surface preparation: shot blasting/ sand blasting recovery e.g. at blasting chamber, ship yard, stripping machine, flooring preparation machine, grinding machine
- heating hose: exterior hose as protection hose

PROPERTIES

- lightweight and reinforced
- highly flexible + compressible 3:1
- abrasion-resistant
- microbe resistant
- good resistance to oil, gasoline and chemicals
- very good low temperature flexibility
- flame-retardant according to: DIN 4102-B1
- flame-retardant according to: UL94-HB
- Permanently antistatic wall: according to ISO 8031 electrical and surface resistance $<10^9 \Omega$ (according to NFPA 652 10^8 - $10^9 \Omega$)
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dust (zone 22 inside), for conveying of non-flammable liquids, for use in zone 1 and 2 (gases)
- conforms to the safety regulations of the German Wood Trade Association
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

DELIVERY VARIANTS

- further diameters and lengths available on request
- transparent (standard)
- special colours: partially coloured, completely coloured
- customer-specific branding
-

DESIGN

- patented PROTAPE® tape hose
- 1. spring steel wire integrated in wall

- 2. wall: permanently antistatic premium ester-polyurethane (Pre-PUR®)
- 3. wall thickness 0,6 mm approx.

TEMPERATURE RANGE

- -40°C to 90°C
- short time to 125°C

Hőállóság: -40°C/+90°C (rövid ideig + 125°C)

Falvastagság a spirálok között mérve: 0,6 mm

Felépítés: poliuretán, áttetsző, beágyazott acélspirállal, hosszában rugalmas

Hajlítási sugár: kb. 1 x belső ø

Lángállóság:: UL94-HB; DIN 4102-B1

Tekercsméret: 10 és 15 m

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Üzemi nyomás DIN 26057 50% hossznyúlás	Vákuum DIN 26057 rögzített végek	Súly kg/m	Cikkszám	Norres cikkszám
25	1,60	-0,54	0,15	102390	330-0025-1002
30	1,35	-0,45	0,18	102902	330-0030-1002
32	1,26	-0,42	0,19	102903	330-0032-1002
38	1,07	-0,35	0,22	102904	330-0038-1002
40	1,02	-0,33	0,23	102905	330-0040-1002
50/51	0,82	-0,22	0,37	102468	330-0050-1002
60	0,68	-0,18	0,43	102906	330-0060-1002
63/65	0,63	-0,16	0,46	102907	330-0065-1002
70	0,59	-0,15	0,50	102908	330-0070-1002
75/76	0,55	-0,14	0,53	102909	330-0075-1002
80	0,51	-0,13	0,57	102686	330-0080-1002
90	0,46	-0,12	0,63	102479	330-0090-1002
100/102	0,41	-0,08	0,67	102910	330-0100-1002
110	0,37	-0,07	0,73	102145	330-0110-1002
120	0,34	-0,07	0,79	102911	330-0120-1002
125/127	0,33	-0,06	0,83	102540	330-0125-1002
140	0,29	-0,05	0,92	102912	330-0140-1002
150/152	0,27	-0,05	0,99	102913	330-0150-1002
160	0,26	-0,05	1,05	102914	330-0160-1002
180	0,23	-0,04	1,17	102915	330-0180-1002
200/203	0,21	-0,03	1,33	102527	330-0200-1002
225	0,18	-0,02	1,48	102916	330-0225-1002



Belső Ø (mm)	Üzemi nyomás DIN 26057 50% hossznyúlás	Vákuum DIN 26057 rögzített végek	Súly kg/m	Cikkszám	Norres cikkszám
250	0,16	-0,02	1,64	102917	330-0250-1002
300	0,14	-0,02	2,14	102918	330-0300-1002
400	0,10	-0,01	2,84	102685	330-0400-1002
500	0,08	-0,01	4,39	102919	330-0500-1002

