

## PTFE corrugated metal braided Corrugated teflon hydraulic hose with metal braiding



### Technical specifications:

It is suitable for the high pressure flow off paint, oil, air, water based liquids and unsaturated steam.

We can deliver to you the hoses assembled with couplings.

**Temperature:** -60°C / +260°C

**Inside:** PTFE Corrugated ASTM D4895, TYPE 1, GRADE4, CLASS B

**Outside:** AISI 304 stainless steel braiding

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

### PTFE corrugated teflon hydraulic hose

DN	Inside diameter (mm)	Wall thickness (mm)	Outer diameter (mm)	Diameter tolerance (mm)	Working / Burst pressure on 20 °C (bar)	Bending radius (mm)	Article Number
10	9,5	0,76	14,75	0,6	138/414	20	200110
13	12,83	0,89	18,8	0,6	103/310	25	200010
16	15,88	0,89	22,1	0,6	83/248	51	200020
19	19,05	0,89	24,65	0,7	69/207	64	200030
25	25,4	1,02	32,77	0,8	46/138	89	200040
32	32,2	1,02	40,72	0,8	34/103	127	200457
38	38,1	1,12	47	0,8	30/90	152	200450
50	51,4	1,1	60	0,8	23/69	200	200165