

PTFE corrugated metal braided Corrugated teflon hydraulic hose with metal braiding



Technical specifications:

It is suitable for the high pressure flow of paint, oil, air, water based liquids and unsaturated steam.

We can deliver to you the hoses assembled with couplings.

Temperature: -60°C / +260°C

Inside: PTFE Corrugated ASTM D4895, TYPE 1, GRADE4, CLASS B

Outside: AISI 304 stainless steel braiding

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

PTFE corrugated teflon hydraulic hose

| DN | Inside diameter (mm) | Wall thickness (mm) | Outer diameter (mm) | Diameter tolerance (mm) | Working / Burst pressure on 20 °C (bar) | Bending radius (mm) | Article Number |
|----|----------------------|---------------------|---------------------|-------------------------|---|---------------------|----------------|
| 10 | 9,5 | 0,76 | 14,75 | 0,6 | 138/414 | 20 | 200110 |
| 13 | 12,83 | 0,89 | 18,8 | 0,6 | 103/310 | 25 | 200010 |
| 16 | 15,88 | 0,89 | 22,1 | 0,6 | 83/248 | 51 | 200020 |
| 19 | 19,05 | 0,89 | 24,65 | 0,7 | 69/207 | 64 | 200030 |
| 25 | 25,4 | 1,02 | 32,77 | 0,8 | 46/138 | 89 | 200040 |
| 32 | 32,2 | 1,02 | 40,72 | 0,8 | 34/103 | 127 | 200457 |
| 38 | 38,1 | 1,12 | 47 | 0,8 | 30/90 | 152 | 200450 |
| 50 | 51,4 | 1,1 | 60 | 0,8 | 23/69 | 200 | 200165 |