

Purflex/L Thin walled polyurethane suction hose with 0,4-0,7 mm wall thickness



Technical specifications:

It is suitable for vacuum cleaners and extraction equipment. The hose is extremely flexible, abrasion, crush, oil and fuel resistant. The wall thickness, between the spirals, is 0,4-0,7 mm.

Felirat: ® PURFLEX / L - SIZE

Heat resistance: -40°C/+90°C (for short time + 125°C)

Structure: polyurethane, transparent, embedded steel helix, corrugated interior and exterior, the thin wall of the slightly bend into between the spirals

Bending radius: 1 x inside ø

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Vacuum (bar)	Weight (kg/m)	Roll size (m)	Article number
25	0,2	0,14	20	4610 025000
32	0,2	0,16	20	4610 032000
38	0,2	0,17	20	4610 038000
40	0,2	0,18	20	4610 040000
45	0,2	0,2	20	4610 045000
51	0,2	0,22	20	4610 050000
60	0,17	0,255	20	4610 060000
70	0,17	0,37	20	4610 070000
75	0,17	0,4	20	4610 075000
80	0,16	0,42	20	4610 080000
90	0,16	0,47	20	4610 090000
102	0,13	0,53	15	4610 100000
110	0,1	0,58	15	4610 110000
120	0,12	0,615	15	4610 120000
125	0,1	0,76	15	4610 125000
130	0,09	0,8	15	4610 130000
140	0,09	0,85	15	4610 140000
152	0,08	0,9	15	4610 150000
160	0,07	0,945	15	4610 160000
180	0,05	1,212	15	4610 180000
203	0,04	1,405	15	4610 200000
254	0,04	1,9	10	4610 250000



TRIÁSZ-TÖMLŐ KFT.

Inside Ø (mm)	Vacuum (bar)	Weight (kg/m)	Roll size (m)	Article number
305	0,03	2,275	10	4610 300000
350	0,03	2,85	10	4610 350000
400	0,02	3,05	10	4610 400000
405	0,02	3,25	10	4610 405000
450	0,01	3,65	10	4610 450000
500	0,01	3,9	10	4610 500000

