

# Safety clamp Two-piece safety clamp



### Technical specifications:

It is made of aluminium to mount Allen bolts and couplings, with collared hose tail, together. The material of it is pressed aluminium. It's available with acid resistant steel design.

**Operating pressure:** 25 bar

**Bolt:** Allen bolts

**Standard:** EN 14420-3

The product is a permanent storage lots. Meantime, we hold the right of selling the stock in products.

Hose inside ø (mm)	Hose wall thickness (mm)	Clamping range (mm)	Article number
13	5	22 - 24	5560 013005
19	6	30 - 33	5560 019006
25	5	34 - 37	5560 025005
25	6	36 - 39	5560 025006
32	5	41 - 44	5560 032005
32	8	47 - 50	5560 032008
32	6	43 - 46	5560 032006
38	5	47 - 50	5560 038005
38	8	53 - 56	5560 038008
38	6,5	50 - 52	5560 038065
38	10	57 - 60	5560 038010
40	7	53 - 56	5560 040007
40	10	58 - 61	5560 040010
50	5	59 - 62	5560 050005
50	6	62 - 64	5560 050006
50	8	64 - 67	5560 050008
50	10	69 - 71	5560 050010
63	6	74 - 77	5560 063006
63	10	84 - 87	5560 063010
63	8	78 - 82	5560 063008
75	6	87 - 90	5560 075006
75	8	88 - 93	5560 075008
75	10	94 - 97	5560 075010
80	8	94 - 97	5560 080008
100	6,5	111 - 115	5560 100065
100	8	114 - 119	5560 100008
100	10	118 - 122	5560 100010
100	12	122 - 126	5560 100012

Hose inside ø (mm)	Hose wall thickness (mm)	Clamping range (mm)	Article number
125	10	143 - 148	5560 125010
150	10	168 - 174	5560 150010
150	13	174 - 180	5560 150013
200	12	222 - 229	5560 200012