

# Safety clamp Two-piece safety clamp



### Technical specifications:

It is made of aluminium to mount Allen bolts and couplings, with collared hose tail, together. The material of it is pressed aluminium. It's available with acid resistant steel design.

**Operating pressure:** 25 bar

**Bolt:** Allen bolts

**Standard:** EN 14420-3

The product is a permanent storage lots. Meantime, we hold the right of selling the stock in products.

| Hose inside ø (mm) | Hose wall thickness (mm) | Clamping range (mm) | Article number |
|--------------------|--------------------------|---------------------|----------------|
| 13                 | 5                        | 22 - 24             | 5560 013005    |
| 19                 | 6                        | 30 - 33             | 5560 019006    |
| 25                 | 5                        | 34 - 37             | 5560 025005    |
| 25                 | 6                        | 36 - 39             | 5560 025006    |
| 32                 | 5                        | 41 - 44             | 5560 032005    |
| 32                 | 8                        | 47 - 50             | 5560 032008    |
| 32                 | 6                        | 43 - 46             | 5560 032006    |
| 38                 | 5                        | 47 - 50             | 5560 038005    |
| 38                 | 8                        | 53 - 56             | 5560 038008    |
| 38                 | 6,5                      | 50 - 52             | 5560 038065    |
| 38                 | 10                       | 57 - 60             | 5560 038010    |
| 40                 | 7                        | 53 - 56             | 5560 040007    |
| 40                 | 10                       | 58 - 61             | 5560 040010    |
| 50                 | 5                        | 59 - 62             | 5560 050005    |
| 50                 | 6                        | 62 - 64             | 5560 050006    |
| 50                 | 8                        | 64 - 67             | 5560 050008    |
| 50                 | 10                       | 69 - 71             | 5560 050010    |
| 63                 | 6                        | 74 - 77             | 5560 063006    |
| 63                 | 10                       | 84 - 87             | 5560 063010    |
| 63                 | 8                        | 78 - 82             | 5560 063008    |
| 75                 | 6                        | 87 - 90             | 5560 075006    |
| 75                 | 8                        | 88 - 93             | 5560 075008    |
| 75                 | 10                       | 94 - 97             | 5560 075010    |
| 80                 | 8                        | 94 - 97             | 5560 080008    |
| 100                | 6,5                      | 111 - 115           | 5560 100065    |
| 100                | 8                        | 114 - 119           | 5560 100008    |
| 100                | 10                       | 118 - 122           | 5560 100010    |
| 100                | 12                       | 122 - 126           | 5560 100012    |

| Hose inside ø (mm) | Hose wall thickness (mm) | Clamping range (mm) | Article number |
|--------------------|--------------------------|---------------------|----------------|
| 125                | 10                       | 143 - 148           | 5560 125010    |
| 150                | 10                       | 168 - 174           | 5560 150010    |
| 150                | 13                       | 174 - 180           | 5560 150013    |
| 200                | 12                       | 222 - 229           | 5560 200012    |