

Saldaform/ red Welding hose for acetylene



Felirat: ISO 3821 - 2MPa (20 BAR) - SIZE - SALDAFORM® - YEAR- LOTNR

Operating pressure: 20 bar

Bursting pressure: 60 bar

Heat resistance: -30°C/+70°C

Interior: rubber, black, smooth

Exterior: red, smooth or corrugated (see it in the chart)

Linings: fabric lining

Standard: ISO 3821 (earlier EN 559)

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Outside Ø (mm) | Roll size (m) | Exterior surface | Article number |
|---------------|---------------------|----------------|---------------|------------------|----------------|
| 6,3 | 3,5 | 13,3 | 50 | corrugated | 3255 006000 |
| 9 | 3,5 | 16 | 50 | corrugated | 3255 009000 |
| 8 | 3,5 | 15 | 50 | corrugated | 3255 008000 |
| 6,3 | 3,5 | 13,3 | 40 | smooth | 3256 006000 |
| 9 | 3,5 | 16 | 40 | smooth | 3256 009000 |
| 12,5 | 5 | 22,5 | 50 | smooth | 3256 013000 |
| 16 | 5 | 26 | 50 | smooth | 3256 015000 |