

## SBR Thick rubber sheeting



### Technical specifications:

A **vastag SBR gumilemez** kiváló kopásállóságot és mechanikai ellenállóságot biztosít, így ideális választás **ipari burkolatokhoz, tömítésekhez, rezgéscsillapításhoz** vagy alátétanyagként. Az SBR (sztírol-butadién) alapanyagú lemez jól tűri a fizikai igénybevételt, és szilárdságának köszönhetően hosszú élettartamot biztosít a mindennapos használat során is.

### Főbb jellemzők:

- Jó **kopás- és szakadásállóság**
- Nagy **mechanikai szilárdság**
- Ipari és műszaki felhasználásra is alkalmas
- **Vastag kivitel** – stabilitást és tartósságot biztosít
- Rugalmas, jól alakítható

### Tipikus felhasználási területek:

- Gép- és járműipar
- Ipari csúszásgátló burkolatok
- Tömítések, alátétek gyártása
- Ütés- és rezgéscsillapító réteggként

A gumilemezt különböző **vastagságban** (pl. 8 mm, 10 mm, 20 mm). A pontos méret és alkalmazási cél ismeretében segítünk a megfelelő típus kiválasztásában.

**Heat resistance:** -20°C / +70°C

**Colour:** black

**Specific weight:** 1,5 g/cm<sup>3</sup>

**Surface:** both sides smooth

**Hardness:** 70° +/-5° Shore A

**Design:** without fabric lining

**Tensile elongation:** 200%

**Tensile strength:**  $\geq 3$  Mpa

**Quality:** SBR

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

Thickness (mm)	Width (mm)	Length (mm)	Article number
20	1000	1000	403500
25	1000	1000	403501
30	1000	1000	403502
40	1000	1000	403503
50	1000	1000	403504