

## Blue silicone tube 45° elbow



### Technical specifications:

The silicone tube has a fabric insertion. It is flexible and has a great heat, UV, ozone resistance. It is also electrically insulating.

Fields of use: automobile industry, auto tuning, auto racing, sailing, industrial engines

Request a quotation!

**Heat resistance:** -60°C / +180°C

**Hardness:** 65°-75° Shore A

**Tensile strength:** 6,0 Mpa

**Linings:** 3-4 layers of polyester fabric reinforcement

**Length:** 150 mm

**Colours:** blue, black

The product is a permanent storage lots. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Inside Ø (inch)	Wall thickness (mm)	Operating pressure (kg/cm <sup>2</sup> )	Bursting pressure (kg/cm <sup>2</sup> )	Article number
6,5	1/4"	4	9,8	29,5	-
8	5/16"	4	9,8	29,5	310084
9,5	3/8"	4	9,8	29,5	-
11	7/16"	4	8	24	310094
13	1/2"	4	8	24	310067
16	5/8"	4	8	24	310086
19	3/4"	4	5,8	17,5	310451
22	7/8"	4	5,8	17,5	310087
25	1"	4,5	5,8	17,5	310066
28	1 1/8"	4,5	5,8	17,5	310088
30	1 3/16"	4,5	4,2	12,5	310059
32	1 1/4"	4,5	4,2	12,5	310061
35	1 3/8"	4,5	4,2	12,5	310089
38	1 1/2"	4,5	3,3	10	310062
40	1 5/8"	4,5	3,3	10	310091
45	1 3/4"	4,5	3,2	9,5	310092
48	1 7/8"	4,5	3,2	9,5	310093
51	2"	5	3,2	9,5	310069
54	2 1/8"	5	3,2	9,5	-
57	2 1/4"	5	2,7	8	-

Inside Ø (mm)	Inside Ø (inch)	Wall thickness (mm)	Operating pressure (kg/cm <sup>2</sup> )	Bursting pressure (kg/cm <sup>2</sup> )	Article number
60	2 3/8"	5	2,7	8	-
63	2 1/2"	5	2,7	8	-
65	2 9/16"	5	2,7	8	-
68	2 11/16"	5	2,5	7,5	-
70	2 3/4"	5	2,5	7,5	-
76	3"	5,5	2,5	7,5	-
80	3 1/8"	5,5	2,5	7,5	-
83	3 1/4"	5,5	1,8	5,5	-
90	3 1/2"	5,5	1,8	5,5	-
102	4"	5,5	1,5	4,5	-
114	4 1/2"	5,5	1,2	3,5	-

