

## Silocord ® / SP Concrete suction/discharge hose



### Technical specifications:

It is suitable for lime, cattle feed and other abrasive medium.

**Felirat:** ® SILOCORD® / SP ZEMENT / DRY - CARGO PN 6 BAR - M

**Operating pressure:** 6 bar

**Heat resistance:** -30°C/+80°C

**Interior:** NR/SBR, black, smooth

**Exterior:** SBR, black, fabric imprinted

**Linings:** steel spiral and steel wire helix

**Vacuum:** 0,8

**Electrical resistance:**  $R < 10^6 \Omega$

**Abrasion resistance:** 70 mm<sup>3</sup> according to ISO 4649 (earlier DIN 53516) standard

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Outside Ø (mm) | Roll size (m) | Article number |
|---------------|---------------------|----------------|---------------|----------------|
| 76            | 10                  | 96             | 40            | 3535 076096    |
| 102           | 10                  | 122            | 20            | 3535 102122    |
| 102           | 10                  | 122            | 28            | 3535 102122    |
| 102           | 10                  | 122            | 40            | 3535 102122    |
| 110           | 10                  | 130            | 40            | 3535 110000    |