

## Silocord® / Alim /SP Abrasion resistant, food quality suction/discharge hose



### Technical specifications:

It is suitable for sugar, powder, PVC-granulate, and grains. Static charge dissipation is possible by grounding the static wire.

The interior is food quality, according to the right standards:

EG 1935-2004 / BfR XXI. 2002 cat. 4 FDA (CFR 21 § 177. 2600)

**Felirat:** ® SILOCORD® / ALIM GRANULATE PN 8 BAR - BfR XXI KAT. 4 - FDA

**Operating pressure:** 8 bar

**Bursting pressure:** 24 bar

**Heat resistance:** -30°C/+80°C

**Interior:** NR/SBR, white, smooth, abrasion resistant, food quality

**Exterior:** SBR, black, fabric imprinted

**Linings:** steel wire spiral, fabric lining and two crossed wire helix

**Vacuum:** -0,8 bar

**Abrasion resistance:** 100 - 110mm<sup>3</sup> according to ISO 4649 (earlier DIN 53516) standard

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Outside Ø (mm) | Roll size (m) | Article number |
|---------------|---------------------|----------------|---------------|----------------|
| 75            | 8                   | 91             | 40            | 3565 075000    |
| 100           | 10                  | 120            | 20            | 3565 100000    |