

## SOLVO-UPE-SP Suction/discharge, FDA, flexible chemical rubber hose with steel helix reinforcement



### Technical specifications:

The universal suction, discharge hose is lightweight, flexible, electrically conductive and solvent resistant. It is suitable for the chemical industry.

**Felirat:** SOLVO - UPE R

**Operating pressure:** 8 bar

**Bursting pressure:** 24 bar

**Heat resistance:** -20°C/+90°C (depending on the transferred medium)

**Interior:** UPE marbled, electrically conductive, smooth, FDA

**Exterior:** corrugated EPDM rubber, black, fabric imprinted, electrically conductive

**Linings:** steel spiral and fabric linings

**Roll size:** 40 m

**Vacuum:** -0,9 bar

**Elektromos ellenállás:** 106 Ω

**Hajlítási sugár:** 4 x inside ø

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Bending radius (mm) | Vacuum (bar) | Weight (kg/m) | Article number |
|---------------|---------------------|---------------------|--------------|---------------|----------------|
| 32            | 9                   | 128                 | -0,9         | 0,83          | 999384         |
| 38            | 6,5                 | 152                 | -0,9         | 1,04          | 999385         |
| 50            | 7                   | 200                 | -0,9         | 1,6           | 999367         |
| 75            | 8                   | 300                 | -0,9         | 2,76          | 999386         |

