

SOLVO-UPE-SP Suction/discharge, FDA, flexible chemical rubber hose with steel helix reinforcement



Technical specifications:

The universal suction, discharge hose is lightweight, flexible, electrically conductive and solvent resistant. It is suitable for the chemical industry.

Felirat: SOLVO - UPE R

Operating pressure: 8 bar

Bursting pressure: 24 bar

Heat resistance: -20°C/+90°C (depending on the transferred medium)

Interior: UPE marbled, electrically conductive, smooth, FDA

Exterior: corrugated EPDM rubber, black, fabric imprinted, electrically conductive

Linings: steel spiral and fabric linings

Roll size: 40 m

Vacuum: -0,9 bar

Elektromos ellenállás: 106 Ω

Hajlítási sugár: 4 x inside ø

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

| Inside Ø (mm) | Wall thickness (mm) | Bending radius (mm) | Vacuum (bar) | Weight (kg/m) | Article number |
|---------------|---------------------|---------------------|--------------|---------------|----------------|
| 32 | 9 | 128 | -0,9 | 0,83 | 999384 |
| 38 | 6,5 | 152 | -0,9 | 1,04 | 999385 |
| 50 | 7 | 200 | -0,9 | 1,6 | 999367 |
| 75 | 8 | 300 | -0,9 | 2,76 | 999386 |

