

## SOLVO-UPE-SP Suction/discharge, FDA, flexible chemical rubber hose with steel helix reinforcement



### Technical specifications:

The universal suction, discharge hose is lightweight, flexible, electrically conductive and solvent resistant. It is suitable for the chemical industry.

**Felirat:** SOLVO - UPE R

**Operating pressure:** 8 bar

**Bursting pressure:** 24 bar

**Heat resistance:** -20°C/+90°C (depending on the transferred medium)

**Interior:** UPE marbled, electrically conductive, smooth, FDA

**Exterior:** corrugated EPDM rubber, black, fabric imprinted, electrically conductive

**Linings:** steel spiral and fabric linings

**Roll size:** 40 m

**Vacuum:** -0,9 bar

**Elektromos ellenállás:** 106 Ω

**Hajlítási sugár:** 4 x inside ø

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Inside Ø (mm)	Wall thickness (mm)	Bending radius (mm)	Vacuum (bar)	Weight (kg/m)	Article number
32	9	128	-0,9	0,83	999384
38	6,5	152	-0,9	1,04	999385
50	7	200	-0,9	1,6	999367
75	8	300	-0,9	2,76	999386

