

## Spurgo/SPL Canal cleaner suction hose



### Technical specifications:

The hose has a strong design with spiral reinforcement. It's suitable for canal cleaner trucks, as a rubber suction hose. It's creased in a small diameter and stays rigid. The hose can be manufactured with different diameters, request a quotation!

**Operating pressure:** 5 bar

**Bursting pressure:** 15 bar

**Heat resistance:** -30°C / +80°C, for short time +100°C

**Interior:** SBR/NBR rubber, black, smooth, abrasion resistant

**Exterior:** SBR/NBR, black, smooth, abrasion resistant rubber, fabric imprinted

**Linings:** strong steel spiral and fabric linings

**Roll size:** 40 m

**Vacuum:** -0,9 bar

The product is a permanent storage lots. Meantime, we hold the right of selling the stock in products.

| Belső Ø (mm) | Falvastagság (mm) | Külső Ø (mm) | Hajlítási sugár (mm) | Súly (kg/m) | Tekercsméret (m) | Cikkszám |
|--------------|-------------------|--------------|----------------------|-------------|------------------|----------|
| 100          | 9                 | 118          | 450                  | 5,35        | 40               | 105025   |
| 110          | 10,5              | 131          | 500                  | 6,2         | 40               | 105032   |
| 120          | 10,5              | 141          | 540                  | 6,6         | 40               | 105033   |
| 125          | 10,5              | 146          | 600                  | 6,8         | 20               | 105031   |
| 150          | 11,5              | 173          | 700                  | 8,8         | 20               | 105034   |