

Three-way ball valve Made of brass with T-bore or L-bore



Technical specifications:

T-bore: type 12800

L-bore: type 12900

It has three female threads.

Operating pressure: 25 bar

Heat resistance: -20°C / +110°C

Ball's sealing: PTFE

Lever: steel, black, varnished

Ball: chrome-plated brass

Body: nickel-plated brass

Certain diameters are available from stock. Meantime, we hold the right of selling the stock in products.

T vagy L furattal

| Femal thread | Flow (mm) | Installment length (mm) | Installment width (mm) | Bore | Article number |
|--------------|-----------|-------------------------|------------------------|------|----------------|
| G 1/4" | 10 | 77 | 58 | T | 5280 006128 |
| G 1/4" | 10 | 77 | 58 | L | 5281 006129 |
| G 3/8" | 12 | 77 | 58 | T | 5280 010128 |
| G 3/8" | 12 | 77 | 58 | L | 5281 010129 |
| G 1/2" | 14 | 77 | 58 | T | 5280 013128 |
| G 1/2" | 14 | 77 | 58 | L | 5281 019129 |
| G 3/4" | 18 | 92 | 70 | T | 5280 019128 |
| G 3/4" | 18 | 92 | 70 | L | 5281 019129 |
| G 1" | 23 | 104 | 80 | T | 5280 025128 |
| G 1" | 23 | 104 | 80 | L | 5281 025129 |