

## Turboflex / U.L. / OHM Conductive, abrasion resistant rubber suction hose, lightweight and flexible



### Technical specifications:

The abrasion resistant rubber hose is suitable for pebbles, tailings and other abrasive medium. It is extremely flexible, lightweight and easy to handle.

**Felirat:** ® TURBOFLEX/UL/OHM - SAUG/DRUCK - SUCTION/DISCHARGE - ABRIEB/ABRASION 60 MM3 - WP 5 BAR - BP 15 BAR - Ω

**Operating pressure:** 5 bar

**Bursting pressure:** 15 bar

**Heat resistance:** -25°C / +80°C

**Interior:** NR6SBR, black, smooth, abrasion-resistant, electrically conductive

**Exterior:** SBR, black, fabric imprinted, corrugated, antistatic

**Linings:** steel wire helix

**Roll size:** 20 m

**Vacuum:** -0,9 bar

**Electrical resistance:** < 10<sup>6</sup> Ohm

**Abrasion value:** 60 mm<sup>3</sup> according to ISO 4649 (earlier DIN 53516)

**Bending radius:** 2,5 x inside ø

Storage lots, splitting of the rolls are possible. Meantime, we hold the right of selling the stock in products.

Belső Ø (mm)	Falvastagság (mm)	Külső Ø (mm)	Súly (kg/m)	Hajlítási sugár (mm)	Tekercsméret (m)	Cikkszám
51	5,5	62	1,31	130	20	3508 050000
63	6	75	1,8	160	20	3508 063000
76	6	88	2,13	190	20	3508 075000
102	6,5	115	3,07	255	20	3508 100000
127	8,5	144	5,11	380	20	3508 125000
152	8,5	169	6,04	460	20	3508 150000