


## SM1® - STRAHLMEISTER

Premium sandblast hose



Marking: SM1® - Sandstrahl-Shotblast-Strahlmeister® PN 12 bar

Norm	ISO 4649 (previous DIN 53516)	Abrasion value tube	36 mm <sup>3</sup>
Working pressure	12 bar	Construction tube	Smooth
Bursting pressure	42 bar	Color tube	Black
Min. temperature	-35 °C	Compound cover	SBR
Max. temperature	+80 °C	Cover	Fabric finish
Electr. resistance tube	Electrical conductive <10 <sup>6</sup> Ω	Color cover	Black
Electr. resistance cover	Antistatic <10 <sup>9</sup> Ω	Reinforcements	Textile plies
Compound tube	SBR/NR/BR		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3501013027	13,0	7,0	27,0	130	0,500	40
3501019033	19,0	7,0	33,0	190	0,650	40
3501025039	25,0	7,0	39,0	250	0,800	40
3501032048	32,0	8,0	48,0	320	1,100	40
3501042060	42,0	9,0	60,0	420	1,650	40

**Application:** The best quality sandblast hose available on the market with a very high quality wear resistant 36mm<sup>3</sup> tube. Suitable for highly abrasive materials such as quartz sand, blasting grit, corundum and glass. This hose is the solution for very heavy applications and has an extremely long lifespan due to the very good abrasion value of the tube.

**Remark:**

- Cutted length not possible

