



## Crush resistant exhaust gas hose

### Applications

- flexible hose/ ducting for hot gases
- vehicle gas exhaust system, car gas extraction: hose reel, slotted floor channel, underfloor extraction system
- engine test bench, exhaust gas measurement

### Properties

- fabric reinforced
- highly flexible + compressible
- protected, flow-optimizing exterior folds
- vibration resistant

- crush resistant
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- exhaust gas temperatures to 200 °C \*
- \* when correctly applied with exhaust gas funnels and sufficient fresh air supply (50% approx.).

### Design

- patented PROTAPE® tape hose

- special plastic-profile supporting spiral
- fabric-reinforced tape
- wall: EPDM/ PP coated fabric
- wall thickness 0,4 mm approx.

### Delivery variants

- further diameters and lengths available on request
- black (standard)
- special colours: coloured spiral
- customer-specific branding

I.D.	outer Ø	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(mm)	(kg/m)	(m)	(m)	
2 / 50-51	68.00	0,400	48.00	0.38	-	10 15	326-0051-0000
2,5 / 63-65	80.00	0,280	53.00	0.48	-	10 15	326-0063-0000
3 / 75-76	93.00	0,170	60.00	0.54	10 15	5 6 7,5 12,5	326-0076-0000
4 / 100-102	119.00	0,050	71.00	0.71	5 7,5 10 15	6 12,5	326-0102-0000
5 / 125-127	144.00	0,035	100.00	0.87	10 15	5 6 7,5 12,5	326-0127-0000
6 / 150-152	169.00	0,030	110.00	1.04	10 15	5 6 7,5 12,5	326-0152-0000
8 / 200-203	220.00	0,010	155.00	1.37	-	5 6 7,5 10 12,5	326-0203-0000

## Accessories



CONNECT 228



CLAMP 217



CONNECT 270-271



CLAMP 213



CLAMP 212