

AGRIFLAT



Layflat water hose

extremely resilient due to heavy tensile inserts.

Marking: Agriflat - dimension

Norm	EN ISO 1307:2008	Compound cover	NBR/PVC
Min. temperature	-20 °C	Cover	Ribbed
Temperature peak	+100 °C	Color cover	Black
Max. temperature hot water	+80 °C	Resistance tube	Oil resistant, Petrol resistant
Compound tube	NBR/PVC	Resistance cover	Ageing resistant, Ozone resistant, UV resistant, Weather resistant
Color tube	Black		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Measured flat (mm)	WP at 20°C (bar)	Max. WP air (bar)	BP (bar)	Weight (kg/mtr)	Length (mtr)
3070019000	20,0	2,0	24,0	30	25,0	18	75	0,180	20/100
3070025000	26,0	2,2	30,4	39	25,0	18	75	0,210	20/100
3070032000	32,0	2,2	36,4	50	20,0	15	60	0,240	100
3070038000	38,0	2,3	42,6	60	16,0	12	50	0,300	20/100
3070050000	52,0	2,5	57,0	82	16,0	12	50	0,400	20/100
3070075000	76,0	2,9	81,8	118	16,0	12	50	0,650	20/100
3070090000	90,0	3,3	96,6	141	16,0	12	50	0,900	100
3070100000	102,0	3,3	108,6	160	16,0	12	50	1,000	20/100
3070125000	127,0	3,5	134,0	196	14,0	10	42	1,400	20/100
3070150000	152,0	3,7	159,4	239	14,0	10	42	1,800	20/50
3070200000	203,0	3,9	210,8	319	10,0	7	30	2,600	50

Application: Hose is used for various agricultural applications (dung transport and irrigation / sprinkling), firefighting, discharge and supply of industrial water (including hot water), pumps, sewer cleaning, cable protection and various other heavy industrial applications. Hose is also suitable for use with air. Limited acid, lye and dung resistant. The inserts are fully embedded in the rubber material, which means there is a very small chance of mechanical damage.

Remark:

- Cutted length possible

We recommend assembly with

5721
Perrot couplings



5110
Storz couplings



6202
Mikalor Supra - clamps

