

# CLAMP 212 EC



Bridge Clamp with integral grounding (via earth strip) for attaching externally corrugated spiral hoses

### Properties

- grounding without exposing spiral and without damaging hose
- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted

- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Design

- Quality: W2; Clamp strip: stainless steel 1.4301 = AISI 304; Screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; Bridge: stainless steel 1.4301 = AISI 304 (INOX)
- in accordance with DIN 3017

### Delivery variants

- further diameters available on request

Suitable for Hose I.D. (mm)	Clamping Range (mm)	Band Width (mm)	Order No.
<b>Clamp with earthing wire</b>			
38-45	35-55	9	212-0035-2878
50-55	45-65	9	212-0045-2878
60-65	55-75	9	212-0055-2878
70-75	65-85	9	212-0065-2878
80-85	75-95	9	212-0075-2878
90-95	85-105	9	212-0085-2878
100-105	95-115	9	212-0095-2878
110-115	105-125	9	212-0105-2878
120-127	115-135	9	212-0115-2878
130-135	125-145	9	212-0125-2878
140-145	135-155	9	212-0135-2878
150-155	145-165	9	212-0145-2878
160-165	155-175	9	212-0155-2878
190-195	185-205	9	212-0185-2878
200-205	195-215	9	212-0195-2878
250-255	245-265	12	212-0245-2878
350-355	345-365	12	212-0345-2878

## Accessories



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).